


# EPS E-BOARD VANDERSANDEN GROUP

	<p><b>Vandersanden Group</b></p> <p>Riemsterweg 300 B-3740 Spouwen (Bilzen) Tel: +32 (0)89 51 01 40 <a href="mailto:info@vandersanden.com">info@vandersanden.com</a></p> <div style="text-align: center;">  </div> <p>Beschermen tegen zonnestralen</p>	<p><b>Lengte:</b> 1200 mm <b>Dikte:</b> 40 - 300 mm <b>Breedte:</b> 532 mm (DF/M65) 558 mm (WF/M50)</p> <p><b>ID No.</b> 1300615002060</p>
--	---	--

	<p>1413 DoP-NL-01-1413-EPS HR 100 SE-Polysteen <a href="http://www.isobouw.nl">www.isobouw.nl</a> No.0461-k-14/1-Kiwa 26-1-2015</p>	<p><b>EN 13163</b></p> <p>DN (mm) 40 - 300 Rd (m<sup>2</sup>K/W) 1,29 - 9,81 RtF-E brandreactie</p>
	<p>EPS EN 13163 - T2 - L3 - W3 - S5 - P5 - DS(N)5 - DS(70,90)1 - CS10 100 - BS150</p>	<p><math>\lambda_D</math> 0,031 W/mK</p>

E-BOARD ISOLATIEDIKTES	
Dikte	Warmteweerstand Rd
40 mm	1,29 m <sup>2</sup> K/W
60 mm	1,94 m <sup>2</sup> K/W
80 mm	2,58 m <sup>2</sup> K/W
100 mm	3,23 m <sup>2</sup> K/W
120 mm	3,87 m <sup>2</sup> K/W
140 mm	4,52 m <sup>2</sup> K/W
160 mm	5,16 m <sup>2</sup> K/W
180 mm	5,81 m <sup>2</sup> K/W
184 mm	5,94 m <sup>2</sup> K/W
204 mm	6,58 m <sup>2</sup> K/W
224 mm	7,23 m <sup>2</sup> K/W
244 mm	7,87 m <sup>2</sup> K/W
264 mm	8,52 m <sup>2</sup> K/W
284 mm	9,16 m <sup>2</sup> K/W
304 mm	9,81 m <sup>2</sup> K/W